


HWF CORE BARREL



	ITEM DESCRIPTION	PART NUMBERS
1 -20	HWF CORE BARREL ASSEMBLY 3.0 M	90-00-100
1 -20	HWF CORE BARREL ASSEMBLY 1.5 M	90-00-110
1-14	HWF HEAD ASSEMBLY	64-00-200
01	HEAD	64-01-001
02	SPINDLE	64-01-002
03	OIL SEALS - 2 NOS.	64-01-003
04	BEARING HOUSING	64-01-004
05	NUT	64-01-005
06	BALL BEARINGS 6205 - 2NOS.	64-01-006
07	M8 BOLT	64-01-007
08	BEARING HOUSING CAP	64-01-008
09	OIL SEAL	64-01-009
10	GREASE FITTING	16-03-024
11	INNER TUBE CAP	90-01-001
12	SPRING DOWELL	64-01-011
13	CASTLE NUT	64-01-012
14	COTTER PIN	64-01-013
15	INNER TUBE 3.0 M	90-03-001
15	INNER TUBE 1.5 M	90-03-002
16	INNER TUBE EXTENTION	90-03-003
17	CORE LIFTER	90-03-004
18	CORE LIFTER CASE	90-03-005
19	OUTER TUBE 3.0 M	90-02-001
19	OUTER TUBE 1.5 M	90-02-002
20	THREAD PROTECTOR	90-02-003

ALL AMKO CORE BARRELS ARE MANUFACTURED FROM THE HIGHEST QUALITY RAW MATERIALS i.e. COLD DRAWN SEAMLESS TUBES OF GRADE SAE 1541 THAT ARE IMPORTED . THESE HAVE EXTREMELY HIGH MECHANICAL PROPERTIES AND STRAIGHTNESS BETTER THAN 1 : 2000 .

STANDARD AMKO CORE BARRELS HAVE HEAT TREATED ALLOY STEEL HEADS WHICH COME WITH HARD METAL STRIPS ON THE DIAMETER OF THE HEAD WHICH ARE 60 Rc TO 65 Rc .

OPTIONALLY WE ALSO SUPPLY STANDARD CORE BARRELS WITH 18" LONG HARD CHROME PLATING AT BOTH ENDS OF THE OUTER TUBE AT EXTRA COST. THIS INCREASES THE LIFE OF THE OUTER TUBE EXPONENTIALLY.