



GALL FREE WIRELINE DRILL ROD



LATEST SURFACE TREATMENT TECHNOLOGY WHICH CREATES MICROSCOPIC LAYER ON THE METAL SURFACE IMPROVING THE WEAR RESISTANCE AND RUST PREVENTION EXPONENTIALLY. IT ALSO ELIMINATES FRICTION COMPLETELY RESULTING IN 100% GALLING FREE DRILL ROD

HEAT TREATED ROD ENDS HARDENED (30 TO 35 Rc) THROUGHOUT THE WALL THICKNESS UPTO A LENGTH OF 200MM

SIZE	LENGTH	O.D.	I.D.	T.P.I	WEIGHT KGS	PART NUMBERS
AWL	1.5M	44.5	34.9	4	7.1	K3-01-001
AWL	3.0M	44.5	34.9	4	14.2	K3-01-002
AT	1.5M	44.5	34.9	2.5	7.0	K3-01-003
AT	3.0M	44.5	34.9	2.5	14.0	K3-01-004
BWL	1.5M	55.6	46	3	8.9	K3-02-001
BWL	3.0M	55.6	46	3	17.9	K3-02-002
BT	1.5M	55.6	46	2.5	8.9	K3-02-003
BT	3.0M	55.6	46	2.5	17.9	K3-02-004
NWL	1.5M	69.9	60.3	3	12	K3-03-001
NWL	3.0M	69.9	60.3	3	23.5	K3-03-002
NT	1.5M	69.9	60.3	2	12.1	K3-03-003
NT	3.0M	69.9	60.3	2	23.6	K3-03-004
HWL	1.5M	88.9	77.8	3	18	K3-04-001
HWL	3.0M	88.9	77.8	3	34.9	K3-04-002
HT	1.5M	88.9	77.8	2	18.2	K3-04-003
HT	3.0M	88.9	77.8	2	35.2	K3-04-004
PWL	1.5M	114.3	101.6	3	28	K3-05-001
PWL	3.0M	114.3	101.6	3	52.5	K3-05-002
PHD	1.5M	114.3	101.6	2.5	28.2	K3-05-003
PHD	3.0M	114.3	101.6	2.5	53	K3-05-004

ALL AMKO WIRELINE DRILL RODS ARE MANUFACTURED FROM THE HIGHEST QUALITY RAW MATERIALS i.e. COLD DRAWN SEAMLESS TUBES OF GRADE SAE 1541 / SAE 4130 / SAE 5130 THAT ARE IMPORTED . THESE HAVE EXTREMELY HIGH MECHANICAL PROPERTIES FOR MID BODY AND STRAIGHTNESS BETTER THAN 1 : 5000 .